



DINO 150ZX

Workhorse of the DINO family



Technical specifications on DINO I 50ZX



| | | |
|------------------------------------|------------------------|------------------------|
| Working height | 15.0 m | 49'3" |
| Platform height | 13.0 m | 42'8" |
| Horizontal reach | 9.0 m | 29'6" |
| Outrigger footprint – width | 3.78 m | 12'5" |
| Lift capacity | 215 kg | 474 lbs |
| Platform size | 0.88 x 1.4 m | 2'11" x 4'7" |
| Boom rotation | continuous | continuous |
| Platform rotation | 60° | 60° |
| Boom control | 2-speed | 2-speed |
| Transport length | 6.60 m | 21'8" |
| Transport width | 1.85 m | 6'1" |
| Transport height | 2.18 m | 7'2" |
| Weight | 1540 kg | 3400 lbs |
| Drive system | standard | standard |
| AC outlet in platform | standard | standard |
| Power source | 110 VAC/240 VAC | 110 VAC/240 VAC |
| Gradeability | 25% | 25% |

Specifications are subject to change without notice.

Manufacturer

DINO Lift®

Dino Lift Oy, Raikkolantie 145, FI-32210 Loimaa, Finland
Tel. +358 2 76 25 900, Fax +358 2 76 27 160
E-mail: dino@dinolift.com, Internet: www.dinolift.com

Dealer



All steel platform with latching gate offers 60 degree rotation.



Optional gas engine features quick couplings to provide additional power source.



DINO drive system provides easy positioning on job site.

