

Platform

0.91 m x 1.83 m low mount platform
Side entry with inward swing gate
Multiple function operation
Full proportional drive joystick control with integral thumb steer switch
Full proportional main boom and swing joystick control
Variable speed dial control for telescope and platform rotate
Selectable creep speed on drive / lift and swing functions
1.83 m articulating jib

180 degree powered platform rotator
Platform console machine status light panel¹
Load sensing system
AC cable to platform

Power & Transmission

Deutz D2011L04 (37kW) diesel engine
Engine distress warning/shut down system²
Gull-wing hoods
Swing-out engine tray
Spark arresting type muffler
Control ADE™ - Advanced Design Electronics System
Hydrostatic drive transmission
Horn

Functional Equipment & Accessories

3 degree tilt alarm and indicator light
15 x 19.5 foam filled lug tread tyres
Fixed-width frame (extending axles not required)
Lifting/tie down lugs
Hour meter
Ground control selector switch with key lock
Platform tool tray
12V DC auxiliary power

Available Options

0.91 m x 2.44 m low mount platform
13 mm air line to platform
Four wheel drive
Four Wheel Steer/Two Wheel Steer/Crab Steer
15 x 19.5 foam filled non marking tyres
Oscillating front axle
On-board 2500W Generator

Available Options

SkyPower™ Package 7,500 watt on-board generator
SkyWelder® Package 250 amp welder in the platform³
Nite-Bright® Package platform mounted lights⁴
Tow Package⁵
All motion alarm
Alarm package⁶
Light package⁷
Head and tail lights
Flashing amber beacon
Plugs & Sockets
Hostile environment package⁸
Catalytic Purifier Muffler
Soft Touch Proximity System
Corner storage tray

¹ Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.

² Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.

³ Available when integrated with the SkyPower™ package.

⁴ Consists of six 40-watt lights, four turntable mounted lights and two platform mounted lights.

⁵ Available only with two wheel drive on models 400S and 460SJ.

⁶ Includes all-motion alarm and flashing amber beacon.

⁷ Includes platform mounted work lights and head & tail lights.

⁸ Includes console cover, boom wipers and cylinder bellows.

**JLG Industries Inc.**

Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Tel: +31 (0)23 565 5665
Fax: +31 (0)23 557 2493
e-mail address: europe@jlg.com
www.jlgeurope.com
An Oshkosh Corporation Company

660SJ

Platform height	20.31 m
Horizontal outreach	17.30 m
Swing (continuous)	360°
Platform capacity – unrestricted	230 kg
Platform rotator (hydraulic)	180°
Jib – overall length	1.83 m
Jib - range of articulation	130° (+70°/-60°)
A. Platform size	0.91 m x 1.83 m
B. Overall width	2.42 m
C. Tailswing (working condition)	1.14 m
D. Stowed height	2.56 m
E. Overall length	10.84 m
F. Stowed length	10.21 m
G. Wheelbase	2.48 m
H. Ground clearance	0.30 m
Machine weight ¹	13,150 kg
Maximum ground bearing pressure	5.27 kg/cm ²
Maximum tyre load	6,455 kg
Drive speed 2WD	7.2 km/h
Drive speed 4WD	6.4 km/h
Gradeability 2WD	30%
Gradeability 4WD	45%
Tyres	15 x 19.5 Foam Filled
Axle oscillation (optional)	0.20 m
Turning radius – inside 2WS	3.66 m
Turning radius – inside 4WS	1.65 m
Turning radius – outside 2WS	5.41 m
Turning radius – outside 4WS	3.45 m
Diesel engine Deutz D2011L04	37 kW
Diesel engine (option) CAT 3.4	47 kW
Fuel tank capacity	148 L
Hydraulic system	141 L
Auxiliary power	12V DC

¹ Certain options or country standards may increase weight and/or dimensions.

