

**Platform**

0.76 m x 1.83 m low mount platform  
 Side entry with inward swing gate  
 Multiple function operation  
 Full proportional drive joystick control with integral thumb steer switch  
 Full proportional main boom and swing joystick control  
 Variable speed dial control for telescope and platform rotate  
 Selectable creep speed on drive / lift and swing functions  
 1.83 m articulating jib  
 180 degree powered platform rotator  
 Platform console machine status light panel <sup>1</sup>  
 Load sensing system  
 AC cable to platform

**Functional Equipment & Accessories**

4 degree tilt alarm and indicator light  
 12 x 16.5 foam filled lug tread tyres  
 Fixed-width frame (extending axles not required)  
 Lifting/tie down lugs  
 Hour meter  
 Ground control selector switch with key lock  
 Platform tool tray  
 12V DC auxiliary power

**Available Options**

SkyWelder® Package 250 amp welder in the platform <sup>3</sup>  
 Tow Package <sup>4</sup>  
 All motion alarm  
 Alarm package <sup>5</sup>  
 Light package <sup>6</sup>  
 Head and tail lights  
 Flashing amber beacon  
 Plugs & Sockets  
 Hostile environment package <sup>7</sup>  
 Catalytic Purifier Muffler  
 Soft Touch Proximity System  
 Corner storage tray

**Available Options**

0.91 m x 1.83 m low mount platform  
 0.91 m x 2.44 m low mount platform  
 13 mm air line to platform  
 Four wheel drive  
 12 x 16.5 foam filled non marking tyres  
 14 x 17.5 foam filled lug tread tyres  
 Semi-track package (includes floating idler system)  
 Oscillating front axle  
 On-board 2500W Generator  
 SkyPower™ Package 7,500 watt on-board generator

**Power & Transmission**

Perkins 404C-22 (37 kW) diesel engine  
 Engine distress warning/shut down system <sup>2</sup>  
 Gull-wing hoods  
 Swing-out engine tray  
 Spark arresting type muffler  
 Control ADE™ - Advanced Design Electronics System  
 Hydrostatic drive transmission  
 Horn

<sup>1</sup> Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.

<sup>2</sup> Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.

<sup>3</sup> Available when integrated with the SkyPower™ package.

<sup>4</sup> Available only with two wheel drive on models 400S and 460SJ.

<sup>5</sup> Includes all-motion alarm and flashing amber beacon.

<sup>6</sup> Includes platform mounted work lights and head & tail lights.

<sup>7</sup> Includes console cover, boom wipers and cylinder bellows.

**JLG Industries Inc.**

Polaris Avenue 63  
 2132 JH Hoofddorp  
 The Netherlands  
 Tel: +31 (0)23 565 5665  
 Fax: +31 (0)23 557 2493  
 e-mail address: europe@jlg.com  
[www.jlgeurope.com](http://www.jlgeurope.com)  
 An Oshkosh Corporation Company



**460SJ**

Platform height	14.02 m
Horizontal outreach	12.34 m
Swing (continuous)	360°
Platform capacity – unrestricted	230 kg
Optional platform capacity	—
Platform rotator (hydraulic)	180°
Jib – overall length	1.83 m
Jib - range of articulation	130° (+70°/-60°)
A. Platform size	0.76 m x 1.83 m
B. Overall width	2.30 m
C. Tailswing (working condition)	0.86 m
D. Stowed height	2.39 m
E. Stowed length	8.84 m
F. Wheelbase	2.34 m
G. Ground clearance	0.32 m
Machine weight <sup>1</sup>	7,850 kg
Maximum ground bearing pressure	4.42 kg/cm <sup>2</sup>
Maximum tyre load	3,357 kg
Drive speed 2WD	7.2 km/h
Drive speed 4WD	7.2 km/h
Gradeability 2WD	30%
Gradeability 4WD	45%
Tyres	12 x 16.5 Foam Filled
Axle oscillation (optional)	0.20 m
Turning radius – inside	2.01 m
Turning radius – outside	5.00 m
Diesel engine Perkins 404C-22	37 kW
Diesel engine (option) CAT C2.2	37 kW
Fuel tank capacity	98 L
Hydraulic system	197 L
Auxiliary power	12V DC

<sup>1</sup> Certain options or country standards may increase weight and/or dimensions.

